from 1915

SERIE 18.75

HP 40/75 - KW 29/55

10/18 cm



165

Mod. Baby B	↤↦ lavoro cm	HP min / max	KW min / max	N.	Kg
130	130	40/50	29/36	42	670
145	145	40/55	29/41	48	720
165	165	50/60	36/44	54	770
185	185	50/65	36/49	60	820
205	205	50/75	36/55	66	870

STANDARD - DIRECT TOOTHED GEARING **Pdf 540 = 220 Rpm**

- Trasmissione diretta
- Griglia di separazione
- Cofano livellatore posteriore
- Trasmissione laterale a catena (+ 20 cm ingombro)
- Albero cardanico protetto con frizione
- Regolazione profondità di lavoro manuale con viti
- Slitte di appoggio laterali
- Coppia dischi anteriori regolabili
- Ruote di livello
- Coppia profilatori
- Rullo compattatore ø 323 mm

- Direct toothed gearing
- Separation grid
- Rear levelling bonnet
- Lateral chain transmission (+20 cm of width)
- Cardan shaft with safety clutch
- Manual working depth adjustment with screws
- Adjustable lateral slides
- A pair of adjustable front discs
- Steadying wheels
- A pair of formers
- Compactor roller Ø 323 mm

ACCESSORI DA RICHIEDERE ALL'ORDINE - ACCESSORIES AVAILABLE ON REQUEST

- Rullo livellatore motorizzato Ø 273
- Rullo packer Ø 273
- Doppio attacco a 3 punti
- Impianto idraulico regol. Profondità lavoro
- Kit attacco seminatrice posteriore
- Kit attacco 3 punti posteriore
- Kit tramoggia spandiconcime 150 kg
- A comando elettrico o idraulico

- Motorized levelling Ø 273
- Packer roller Ø 273
- 3-Point double hitch
- Hydraulic system for working depth adjustment
- Rear attacchment for seeder
- Rear 3-point hitch
- Spreader hopper kit for 150 kg with adjustable electric or hydraulic command